

# Grundix BetonContact

Contact primer with quartz



## Description:

Grundix BetonContact is pasty primer that improves the adhesion between the gypsum plaster and smooth concrete surfaces.

Grundix BetonContact is ready to use.

## Applications:

Grundix BetonContact provides adhesion between all types of smooth concrete surfaces with minimal water absorption and gypsum machine plasters. Contains organic binders and selected quartz sand, which make an excellent bond between the plaster and surface. Recommended for:

- ▲ smooth concrete
- ▲ ceilings of finished concrete elements
- ▲ precast concrete elements

## Advantages:

- ▲ Excellent adhesion to the concrete
- ▲ One-component, ready to use material
- ▲ Easy application
- ▲ Exterior and interior use
- ▲ Prevent water loss from the plaster to the surface
- ▲ Improves the mortar workability in its application

## Standards:

Grundix BetonContact complies with EN 13300:2004.

## Method of Use

### Surface Preparation:

Surfaces should be clean, sound, dry. As well as free from oil, grease, dirt and loose particles.

### Application:

Stir well Grundix BetonContact with slow-speed paddle. Grundix BetonContact is applied by brush, roller or spray machine. Do not dilute the material .

Leave to dry for 12 hours, depending on the specific conditions. In cool, damp weather drying may last longer. The surface must be completely dry and not sticky to touch before applying gypsum coverage.

## Notes:

- ▲ Grundix BetonContact is used only at temperatures of the surface, air and material itself above 5 ° C.
- ▲ Not apply on wet, frozen or covered with condensation surfaces.

### Technical Properties, 23°C :

Density:	1.52 ± 0.05 g/cm <sup>3</sup>
Dry content:	65,96 %
Adhesion:	2.8 N/mm <sup>2</sup>
Drying:	< 3 h
Liquid water permeability:	0.4 kg/ m <sup>2</sup> .h <sup>0,5</sup>
Particle size, maximum:	> 300 < 1500 µm
Appearance:	paste
pH:	7.5

## Cleaning:

All tools and equipment should be cleaned immediately after use with clean water.

## Packaging:

Grundix BetonContact is available in packs: 1.2 kg, 5 kg, 20, 25 kg.

## Coverage:

Approx. 250 - 300 g/m<sup>2</sup> , depending on substrate.

## Storage:

Grundix BetonContact has shelf life of 12 months if stored in proper conditions, at temperatures range between + 5°C and 35°C in its original unopened packing.

## Cautions

### Health and Safety:

Grundix BetonContact does not fall within the list of dangerous substances according to current regulations.

# Grundix BetonContact

Avoid contact with skin and eyes.

Sprayed places on the skin should immediately be washed with water.

In case of contact with eyes wash immediately with plenty of water and seek medical advice.

## Fire:

Grundix BetonContact is non-flammable.

For further information refer to the Safety Data Sheet.

## More from Don Construction Products

A wide range of construction chemicals products are manufactured by DCP which include:


- ▲ Concrete admixtures.
- ▲ Grouts and chemical fixings.
- ▲ Concrete repairs.
- ▲ Industrial floorings.
- ▲ Structural protection.
- ▲ Waterproofing.

### Note:

We endeavor to ensure that any advice, recommendation or information we may give in product literature is accurate and correct. However, due to the fact that we have no direct or continuous control over where or how the products are applied, DCP cannot accept any liability either directly or indirectly arising from the use of DCP products, whether or not in accordance with any advice, specification, recommendation or information given by us.

 expertise

 quality

 full range

[www.dcp-int.com](http://www.dcp-int.com)