

Beautiful, innovative large-format perforated gypsum panels create unique spaces.



Varina Library | Photo: ©Chris Cunningham Photography

APPLICATIONS


- Conference Rooms
- Classrooms
- Offices
- Airports
- Public Lobbies
- Other Commercial Buildings / Space Applications




Line 6




Quattro 41



Sixto 63



Sixto 65



Quattro 46

FEATURES AND BENEFITS

- Smooth, paintable surface simplifies installation and maintenance, ensuring long, sustainable life
- Screw attach to CertainTeed Drywall Suspension System
- Complementary Gyptone lay-in ceiling panels available for each pattern
- Designed with four tapered edges for easy finishing
- Suitable for wall and ceiling applications and can be shaped to 20-ft radius
- Proprietary Saint-Gobain formaldehyde scavenging performance (inherent to all Gyptone products)
- Environmental Product Declaration (EPD) and Health Product Declaration (HPD) available



Gyptone BIG access panels are quick to install and virtually invisible because the gap between the ceiling and the hatch is minimal. This fully integrated solution is available for most Gyptone BIG patterns and allows for easy access to the plenum. (Not available for Gyptone BIG Sixto 65)

LEED® v4

RECYCLED CONTENT 85%

<input type="checkbox"/>	EA: Optimize Energy Performance
<input type="checkbox"/>	EA: Prereq. Min. Energy Performance
<input checked="" type="checkbox"/>	EQ: Interior Lighting
<input checked="" type="checkbox"/>	MR: PBT Source Reduction (Healthcare)
<input checked="" type="checkbox"/>	EQ: Acoustic Performance
<input checked="" type="checkbox"/>	EQ: Prereq. Min. Acoustic Performance (Schools)
<input checked="" type="checkbox"/>	EQ: Low-Emitting Materials
<input type="checkbox"/>	EQ: Daylight
<input checked="" type="checkbox"/>	MR: Material Ingredients (HPDs)
<input checked="" type="checkbox"/>	MR: Sourcing Raw Materials
<input checked="" type="checkbox"/>	MR: Environmental Product Declarations (EPDs)
<input type="checkbox"/>	MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.






All products in this line
feature these attributes:



LINE 6	Dimensions mm (≈ in.)	NRC	CAC	Hole Size (mm)	Perforated Area	Recycled Content	Max Pieces/ pallet	Sq. m (in.)/ piece	Lbs./ pallet
5200605112	2400 x 1200 x 12.5 (≈ 94.5 x 47.2 x 1/2)	Ceiling: 0.60* Wall: 0.65†	35•	6 x 80	13%	85%	45	3 (31)	2286
QUATTRO 41	Dimensions mm (≈ in.)	NRC	CAC	Hole Size (mm)	Perforated Area	Recycled Content	Max Pieces/ pallet	Sq. m (in.)/ piece	Lbs./ pallet
5200605090	2400 x 1200 x 12.5 (≈ 94.5 x 47.2 x 1/2)	Ceiling: 0.70* Wall: 0.80†	35•	12	16%	85%	45	3 (31)	2286
QUATTRO 46	Dimensions mm (≈ in.)	NRC	CAC	Hole Size (mm)	Perforated Area	Recycled Content	Max Pieces/ pallet	Sq. m (in.)/ piece	Lbs./ pallet
5200640995	2400 x 1200 x 12.5 (≈ 94.5 x 47.2 x 1/2)	Ceiling: 0.60* Wall: 0.60†	35•	12	10%	85%	45	3 (31)	2286
SIXTO 63	Dimensions mm (≈ in.)	NRC	CAC	Hole Size (mm)	Perforated Area	Recycled Content	Max Pieces/ pallet	Sq. m (in.)/ piece	Lbs./ pallet
5200545808	2400 x 1200 x 12.5 (≈ 94.5 x 47.2 x 1/2)	Ceiling: 0.65* Wall: 0.70†	35•	12	15%	85%	45	3 (31)	2295
SIXTO 65	Dimensions mm (≈ in.)	NRC	CAC	Hole Size (mm)	Perforated Area	Recycled Content	Max Pieces/ pallet	Sq. m (in.)/ piece	Lbs./ pallet
5200607125	2700 x 900 x 12.5 (≈ 106.3 x 35.4 x 1/2)	Ceiling: 0.75* Wall: 0.85†	35•	12	17%	85%	45	3 (26.1)	1926

*NRC value when used with CertainTeed Sustainable™ Insulation in unfaced 2-1/2" (R-8) as an overlay above the installed ceiling panel
†NRC value when used with CertainTeed Sustainable Insulation in unfaced 2-1/2" (R-8) in wall cavity
•CAC value when used with CertainTeed Sustainable Insulation in unfaced 3-1/2" (R-11) as an overlay above the panel
(Line 6, Quattro 41, Quattro 46 - without insulation NRC=0.55, CAC=17)
(Sixto 63 - without insulation NRC=0.60, CAC=17)
(Sixto 65 - without insulation NRC=0.65, CAC=17)

ACCESSORIES

GYPTONE BIG ACCESSORIES	Product Name	Pieces/carton	Use
—	5200428567 Quattro 41 Access Panel	1	Access Panel for Quattro 41 Ceiling
—	5200428599 Line 6 Access Panel	1	Access Panel for Line 6 Ceiling
—	5200428548 Sixto 63 Access Panel	1	Access Panel for Sixto 63 Ceiling
—	5200428576 Quattro 46 Access Panel	1	Access Panel for Quattro 46 Ceiling
	5200412213 C-Channel	12	For use in framing the perimeter of the wall structure in a Gyptone BIG or Gyptone BIG Curve wall application
	5200412216 Z-Channel	12	For use in framing horizontally across the wall structure in a Gyptone BIG or Gyptone BIG Curve wall application
	5200412717 QSTR 25 Screw	1000	For use when installing Gyptone BIG boards to metal framing

Access panel not available for Gyptone® Big™ Sixto 65

PHYSICAL DATA

MATERIAL
Gypsum

ASTM E1264 CLASSIFICATION
Type XX, Pattern A G

FIRE CLASS (ASTM E1264)
Tested according to ASTM E84 & CAN S102
Flame Spread: 25 or less
Smoke Developed: 50 or less

VOC EMISSIONS
Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

MAINTENANCE
Wipe with a soft cloth or vacuum with brush attachment. Painted surfaces can be cleaned with a damp cloth and mild detergent.



CertainTeed

CEILINGS • DECKING • FENCE • GYPSUM • INSULATION • RAILING • ROOFING • SIDING • TRIM
20 Moores Road Malvern, PA 19355 Professional: 800-233-8990 Consumer: 800-782-8777 certainteeted.com

